





Fire fighting fitting

Storz Coupling

Storz couplings have an identical locking head with no separate male or female halves, and are available in male or female threads, or serrated hose tails for fitting into rubber hose. It can be connected to another style with the same distance between locking ears (KA). Blank caps are available for shutting off delivery when not in use.

Material / Materiał

1. Aluminium by forging and die casting
2. Stainless steel AISI 316 by investment casting
3. Brass in forging

Seal / Uszczelki

Profiled seal in NBR, Viton
Thread seal in PTFE for Stainless steel, NBR for AL.

Info: / informacje:

1. Thread : BSP EN ISO 228, NPT, NPSH, NH
BSP EN ISO 228, NPT, NPSH, NH
2. The AL shank in forging or casting is available
3. Lug Distance (KA/mm):

KA: D = 31
C = 66
B = 89
A = 133







Fire Fighting Fitting
Storz couplings according to DIN

Suction hose coupling / Łącznik ssawny				AL			SS			BR		
BOD Name	KA mm	D mm	L mm	BOD Code	Weight	Price	BOD Code	Weight	Price	BOD Code	Weight	Price
SZT25/20	31	20	53	SZT25020AL	0.09	2,47	SZT25020SS		37,00	SZT25020BR		7,13
SZT25/25	31	24.5	53	SZT25025AL	0.09	2,47	SZT25025SS	0.26	20,64	SZT25025BR		5,19
SZT32/25	44	24.5	70	SZT32025AL	0.14	6,50	SZT32025SS			SZT32025BR	0.42	12,91
SZT32/32	44	32	90	SZT32032AL	0.19	6,50	SZT32032SS		25,67	SZT32032BR		12,91
SZT38/32	51	32	90	SZT38032AL	0.21	6,50	SZT38032SS			SZT38032BR		12,91
SZT38/38	51	38	90	SZT38038AL	0.22	6,50	SZT38038SS		25,67	SZT38038BR		12,91
SZT45/45	59	45	72	SZT45045AL	0,20	4,95	SZT45045SS			SZT45045BR		
SZT52/25	66	24.5	90	SZT52025AL	0.37	4,80	SZT52025SS	0.98	56,05	SZT52025BR	1.01	12,96
SZT52/32	66	32	90	SZT52032AL	0.37	4,29	SZT52032SS	0.98	56,05	SZT52032BR	1.04	12,96
SZT52/38	66	38	90	SZT52038AL	0.37	4,29	SZT52038SS	0.98	41,80	SZT52038BR	1.01	12,96
SZT52/45	66	45	90	SZT52045AL	0.37	4,29	SZT52045SS		54,15	SZT52045BR	1.14	12,96
SZT52/50	66	50	90	SZT52050AL	0.37	4,29	SZT52050SS		61,75	SZT52050BR		
SZT52/52	66	52	90	SZT52052AL	0.37	3,53	SZT52052SS	0.95	26,22	SZT52052BR	1.06	8,21
SZT52/60	66	60	90	SZT52060AL	0.40	4,29	SZT52060SS			SZT52060BR		
SZT52/64	66	64	90	SZT52064AL	0.41	6,08	SZT52064SS			SZT52064BR		
SZT65/38	81	38	90	SZT65038AL	0.46	5,28	SZT65038SS		75,52	SZT65038BR	1.41	17,07
SZT65/52	81	52	95	SZT65052AL	0.50	5,28	SZT65052SS	1.44	59,85	SZT65052BR		15,99
SZT65/63	81	63	95	SZT65063AL	0.49	5,28	SZT65063SS			SZT65063BR		
SZT65/65	81	65	95	SZT65065AL	0.53	5,28	SZT65065SS		39,06	SZT65065BR		15,99
SZT65/75	81	75	95	SZT65075AL	0.53	5,43	SZT65075SS	1.46	75,05	SZT65075BR		16,53
SZT75/52	89	52	125	SZT75052AL	0.66	8,22	SZT75052SS			SZT75052BR		
SZT75/63	89	63	125	SZT75063AL	0.68	6,19	SZT75063SS			SZT75063BR		
SZT75/65	89	65	125	SZT75065AL	0.68	6,19	SZT75065SS		74,25	SZT75065BR		19,28
SZT75/75	89	75	125	SZT75075AL	0.71	5,28	SZT75075SS		49,10	SZT75075BR	2.08	19,07
SZT90/90	105	90	160	SZT90090AL	1.09	14,55	SZT90090SS			SZT90090BR		
SZT100/100	115	100	150	SZT100100AL	1.15	12,35	SZT100100SS	3.78	261,25	SZT100100BR	3,08	80,09
SZT110/100	133	100	170	SZT110100AL	1.77	11,89	SZT110100SS		122,55	SZT110100BR	5,37	69,02
SZT110/110	133	110	170	SZT110110AL	1.66	12,27	SZT110110SS	4.25	110,38	SZT110110BR	5,38	73,98
SZT150/150	160	150	180	SZT150150AL	2.90		SZT150150SS		384,75	SZT150150BR	8,40	142,31



Fire Fighting Fitting
Storz couplings according to DIN

Storz Reducer Przełącznik  SZTR				AL 			SS 			BR 		
BOD Name	KA mm	D mm	L mm	BOD Code	Weight	Price	BOD Code	Weight	Price	BOD Code	Weight	Price
SZTR52/25	66/31	52/25	33	SZTR5225AL	0.31	8,47	SZTR5225SS	1,28	93,10	SZTR5225BR	1,32	28,46
SZTR75/52	89/66	75/52	39	SZTR7552AL	0.60	9,93	SZTR7552SS	2,17	104,50	SZTR7552BR	1,77	35,32
SZTR110/75	133/89	110/75	48	SZTR11075AL	1.57	19,87	SZTR11075SS	4,46	275,00	SZTR11075BR	4,44	123,72


Storz female thread Nasada z gwintem wew. 				AL 			SS 			BR 		
BOD Name	KA mm	D mm	L mm	BOD Code	Weight	Price	BOD Code	Weight	Price	BOD Code	Weight	Price
SZTF25/13	31	G1/2"	30	SZTF25012AL	0.08	3,85	SZTF25012SS		18,98	SZTF25012BR		7,13
SZTF25/20	31	G3/4"	30	SZTF25034AL	0.08	3,76	SZTF25034SS		39,90	SZTF25034BR		7,13
SZTF25	31	G1"	30	SZTF25001AL	0.08	2,71	SZTF25001SS	0.21	23,75	SZTF25001BR	0.23	4,92
SZTF32/25	44	G1"	31	SZTF32001AL	0.08	6,08	SZTF32001SS			SZTF32001BR		11,56
SZTF32	44	G1 1/4"	31	SZTF32114AL	0.14	5,81	SZTF32114SS		22,32	SZTF32114BR	0.39	11,56
SZTF38/25	51	G1"	33	SZTF38001AL	0.15	6,76	SZTF38001SS			SZTF38001BR		13,56
SZTF38/32	51	G1 1/4"	33	SZTF38114AL	0.17	6,11	SZTF38114SS		56,05	SZTF38114BR		12,10
SZTF38	51	G1 1/2"	33	SZTF38112AL	0.15	4,80	SZTF38112SS	0.47	22,32	SZTF38112BR	0.44	11,34
SZTF38/52	51	G2"	37.5	SZTF38002AL	0.18	5,64	SZTF38002SS			SZTF38002BR		13,56
SZTF45/52	59	G2"	35	SZTF45002AL	0.24	6,76	SZTF45002SS			SZTF45002BR		
SZTF52/25	66	G1"	35.5	SZTF52001AL	0.28	4,71	SZTF52001SS		41,80	SZTF52001BR		12,42
SZTF52/32	66	G1 1/4"	35.5	SZTF52114AL	0.30	4,10	SZTF52114SS		42,75	SZTF52114BR		12,42
SZTF52/38	66	G1 1/2"	35.5	SZTF52112AL	0.28	4,10	SZTF52112SS		38,95	SZTF52112BR		12,42
SZTF52	66	G2"	40	SZTF52002AL	0.28	3,34	SZTF52002SS	0.77	22,32	SZTF52002BR	0.80	7,20
SZTF52/65	66	G2 1/2"	40	SZTF52212AL	0.28	4,80	SZTF52212SS		84,55	SZTF52212BR		13,56
SZTF65/25	81	G1"	36	SZTF65001AL	0.53	9,00	SZTF65001SS			SZTF65001BR		
SZTF65/32	81	G1 1/2"	36	SZTF65112AL	0.45	7,56	SZTF65112SS			SZTF65112BR		
SZTF65/52	81	G2"	40.5	SZTF65002AL	0.38	5,47	SZTF65002SS		44,65	SZTF65002BR		15,45
SZTF65	81	G2 1/2"	40.5	SZTF65212AL	0.38	5,47	SZTF65212SS	1.02	33,47	SZTF65212BR	1.12	15,72
SZTF65/75	81	G3"	39	SZTF65003AL	0.41	6,76	SZTF65003SS			SZTF65003BR		20,69
SZTF75/52	89	G2"	41	SZTF75002AL	0.43	6,27	SZTF75002SS		56,05	SZTF75002BR		19,28
SZTF75/65	89	G2 1/2"	42	SZTF75212AL	0.42	4,29	SZTF75212SS		41,80	SZTF75212BR		13,56
SZTF75	89	G3"	41.5	SZTF75003AL	0.42	4,75	SZTF75003SS	1.26	35,15	SZTF75003BR	1.50	19,61
SZTF100	115	G4"	48	SZTF10004AL	0.85	11,59	SZTF10004SS		185,25	SZTF10004BR		60,21
SZTF110	133	G4"	48	SZTF11004AL	1.09	11,59	SZTF11004SS	3.25	94,84	SZTF11004BR	3.77	61,83
SZTF110/115	133	G4 1/2"	48	SZTF11412AL	1.09	12,84	SZTF11412SS	3.25	128,25	SZTF11412BR	3.77	63,51



Fire Fighting Fitting
Storz couplings according to DIN

BOD Name	KA mm	D mm	L mm	BOD Code	Weight	Price	BOD Code	Weight	Price	Code	Weight	Price
SZTF75	89	G3"	41.5	SZTF75003AL	0.42	4,75	SZTF75003SS	1.26	35,15	SZTF75003BR	1.50	19,61
SZTF100	115	G4"	48	SZTF10004AL	0.85	11,59	SZTF10004SS		185,25	SZTF10004BR		60,21
SZTF110	133	G4"	48	SZTF11004AL	1.09	11,59	SZTF11004SS	3.25	94,84	SZTF11004BR	3.77	61,83
SZTF110/115	133	G4 1/2"	48	SZTF11412AL	1.09	12,84	SZTF11412SS	3.25	128,25	SZTF11412BR	3.77	63,51

Storz male thread
Nasada z gwintem zew.



AL



SS




BR



BOD Name	KA mm	D mm	L mm	BOD Code	Weight	Price	BOD Code	Weight	Price	BOD Code	Weight	Price
SZTM25/13	31	G1/2"	33	SZTM25012AL	0.07		SZTM25012SS		38,00	SZTM25012BR		9,62
SZTM25/20	31	G3/4"	33	SZTM25034AL	0.07	3,85	SZTM25034SS		37,05	SZTM25034BR		7,67
SZTM25	31	G1"	33	SZTM25001AL	0.07	3,38	SZTM25001SS	0.21	18,98	SZTM25001BR	0.22	6,92
SZTM32/25	44	G1"	34	SZTM32001AL	0.12	6,27	SZTM32001SS			SZTM32001BR		12,10
SZTM32	44	G1 1/4"	34	SZTM32114AL	0.14	6,27	SZTM32114SS		22,32	SZTM32114BR	0.40	12,10
SZTM38	51	G1 1/2"	32.5	SZTM45112AL	0.14		SZTM45112SS	0.45		SZTM45112BR	0.40	
SZTM52/25	66	G1"	30	SZTM52001AL	0.25		SZTM52001SS			SZTM52001BR		12,96
SZTM52/32	66	G1 1/4"	30	SZTM52114AL	0.25	4,33	SZTM52114SS		50,35	SZTM52114BR		12,96
SZTM52/38	66	G1 1/2"	34	SZTM52112AL	0.25	4,23	SZTM52112SS		45,55	SZTM52112BR		12,96
SZTM52	66	G2"	36	SZTM52002AL	0.21	3,53	SZTM52002SS	0.71	22,32	SZTM52002BR	0.84	9,62
SZTM65/38	81	G1 1/2"	35.5	SZTM65112AL	0.36	9,12	SZTM65112SS			SZTM65112BR		
SZTM65/52	81	G2"	37.5	SZTM65002AL	0.36	5,70	SZTM65002SS		54,15	SZTM65002BR		18,74
SZTM65	81	G2 1/2"	37.5	SZTM65212AL	0.38	5,70	SZTM65212SS	1.07	33,47	SZTM65212BR	1.15	18,74
SZTM65/75	81	G3"	37.5	SZTM65003AL	0.33	7,22	SZTM65003SS			SZTM65003BR		20,69
SZTM75/65	89	G2 1/2"	38	SZTM75212AL	0.36	5,56	SZTM75212SS		52,25	SZTM75212BR		20,15
SZTM75	89	G3"	38	SZTM75003AL	0.39	5,56	SZTM75003SS	1.32	35,15	SZTM75003BR	1.34	21,28
SZTM110	133	G4"	47	SZTM11004AL	1.01	13,35	SZTM11004SS	2.92	94,98	SZTM11004BR	3.15	68,48

Storz Blind Cap With Chain
Pokrywa z łańcuszkiem



AL



SS



BR



BOD Name	KA mm	L mm	BOD Code	Weight	Price	BOD Code	Weight	Price	BOD Code	Weight	Price
SZTC25	31	28	SZTC25AL	0.09	2,68	SZTC25SS	0.25	18,98	SZTC25BR	0.26	5,46
SZTC32	44	27.5	SZTC32AL	0.13	6,08	SZTC32SS		22,32	SZTC32BR	0.37	11,20
SZTC38	51	34	SZTC38AL	0.17	6,08	SZTC38SS	0.50	22,32	SZTC38BR	0.50	11,24
SZTC45	59	32	SZTC45AL		7,79	SZTC45SS			SZTC45BR		
SZTC52	66	43	SZTC52AL	0.38	3,76	SZTC52SS	0.88	22,32	SZTC52BR	0.92	7,94
SZTC65	81	35	SZTC65AL	0.46	5,47	SZTC65SS	1.27	33,47	SZTC65BR	1.27	14,64
SZTC75	89	45	SZTC75AL	0.56	5,28	SZTC75SS	1.34	35,15	SZTC75BR	1.46	15,72
SZTC90	105	43	SZTC90AL		14,55	SZTC90SS			SZTC90BR		
SZTC100	115	48	SZTC100AL	0.56	12,84	SZTC100SS	1.34	213,75	SZTC100BR	1.46	71,23
SZTC110	133	48	SZTC110AL	1.34	12,35	SZTC110SS	3.65	94,84	SZTC110BR	3.73	65,72

Fire Fighting Fitting
Storz couplings according to DIN

Suction special hose couplings												
BOD Name	KA mm	D mm	L mm	BOD Code	Weight	Price	BOD Code	Weight	Price	BOD Code	Weight	Price
SZST25	31	21	50	SZST25021AL	0.10		SZST25021SS			SZST25021BR		
SZST52	66	51	90	SZST52051AL	0.37		SZST52051SS			SZST52051BR		
SZST75	89	76	125	SZST75076AL	0.88		SZST75076SS			SZST75076BR		
SZST102	133	102	170	SZST102102AL	1.80		SZST102102SS			SZST102102BR		
SZST110	133	110	170	SZST110110AL	1.70		SZST110110SS			SZST110110BR		
SZST150	160	150	180	SZST150150AL			SZST150150SS			SZST150150BR		
SZDT25	31	25.4	69	SZDT25025AL	0.12		SZDT25025SS			SZDT25025BR		
SZDT52/25	66	25.4	90	SZDT52025AL			SZDT52025SS			SZDT52025BR		
SZDT52/38	66	38.4	90	SZDT52038AL	0.40		SZDT52038SS			SZDT52038BR		
SZDT52/50	66	50.4	90	SZDT52050AL	0.41		SZDT52050SS			SZDT52050BR		
SZDT75/63	89	63.4	125	SZDT75063AL	0.72		SZDT75063SS			SZDT75063BR		
SZDT75	89	75.4	125	SZDT75075AL	0.71		SZDT75075SS			SZDT75075BR		
SZDT110/100	133	100.3	170	SZDT110100AL	1.68		SZDT110100SS			SZDT110100BR		
SZDT150	160	150	250	SZDT150150AL	3.61		SZDT150150SS			SZDT150150BR		

Storz Long male thread Nasada dłuż. gw. 												
BOD Name	KA mm	D mm	L mm	BOD Code	Weight	Price	BOD Code	Weight	Price	BOD Code	Weight	Price
SZTLM25	31	G1"	44	TLM25001AL			TLM25001SS			TLM25001BR		
SZTLM32	44	G1 1/4"		TLM32114AL			TLM32114SS			TLM32114BR		
SZTLM38	51	G1 1/2"	51	TLM38112AL	0.22		TLM38112SS			TLM38112BR		
SZTLM52	66	G2"	60	TLM52002AL			TLM52002SS			TLM52002BR		
SZTLM65	81	G2 1/2"	62.5	TLM65212AL	0.65		TLM65212SS			TLM65212BR		
SZTLM75	89	G3"	63.5	TLM75003AL			TLM75003SS			TLM75003BR		
SZTLM110	133	G4"		TLM11004AL			TLM11004SS			TLM11004BR		





BODtech Sp. z o.o.
ul. Mszańska, 1a
44-304 Wodzisław Śląski

bodtech@bodtech.pl
tel. +48 503834570
skype: bodtech